

METAPACE

Metapace C-1 – The New Dimension of Card Printing

www.metapace.com

Highlights

- Professional card printer for ID cards, name tags, customer cards and much more
- Produces plastic cards in full-colour and top quality of 12/mm (300 dpi)
- Single or automatic feed feed, holds a supply of 100 cards or more
- Includes card printing software with a wide range of functions (full version)
- Optional magnetic, smart card or RFID encoder

Technical specifications

Print

Technology	Dye sublimation (colour), thermal transfer (monochrome)
Printing speed	Multi-coloured: 26sec.; monochrome:: 4 sec.
Printing pages	Single-sided (option: double-sided)
Resolution	12 dots/mm (300 dpi)
Colour	Full colour
Feeder	Single feeder, stack feeder (for 100 cards or more); output tray (70 cards or more)
Ink ribbon	200 cards/roll (YMCKO); 500 cards/roll (KO)

Electronics

CPU	32-bit processor
Memory	16MB
User interface	LCD, LED, switch
Power supply	Input: AC 100V ~ 240V; 50Hz ~ 60Hz; output: DC 24V
Fonts	True Type fonts via Windows driver
Service life	1 x 108 pulses; print head life: 50 km

Cards

Quality and dimensions (WxL)	PVC - ISO CR-80-ISO 7810; (53.98 x 85.7 x 0.2mm ~ 1.2mm)
------------------------------	--

Encoding (optional)

Magnetic stripe	ISO7811 (tracks 1,2,3), HiCo/LoCo
Contact (IC)	ISO7816, EMV, K-cash
Contactless (RF)	ISO14443 A,B, ISO 15693, MiFare

Interfaces

I/F ports	USB 2.0, RS232; optional: Ethernet 10/100Mbps (TCP/IP)
-----------	--

Software

Drivers	Windows 2000, XP (32-bit), Vista (32 bit), Windows 7 (32 bit/64 bit)
---------	--

Environment


Operating temperature	0°C ~ 50°C
Storage temperature	-25°C ~ 70°C
Humidity	20% ~ 90% RH (non-condensing)

Housing

Dimensions (WxHxD)	192 x 202 x 403mm
Weight	5.5 kg

Warranty

Period	24 months
--------	-----------



**PROFESSIONAL
SOFTWARE
INCLUDED**



C-1

METAPACE